



Beton SHimi
بتن شیمی زرین کوه

Spacer(Beton SHimi)

Double plastic spacer:

A double spacer was used to create a suitable cover in the double mesh slabs. The double spacer consists of two parts, male and female. This spacer is produced in different sizes. The number of use of these double spacers in the concrete slab is 4 per square meter.

Technical specifications of the double spacer

Name	size	Bar size	Packing(QTY)
Double spacer 100	100	8-32	500
Double spacer 120	120	8-32	300
Double spacer 150	150	8-32	250

Advantages of using plastic spacers:

- Rapid production process of plastic spacer
- Ability to produce plastic spacers in different shapes
- High resistance of plastic spacers
- Easy transportation due to light weight and suitable packaging
- Economic efficiency due to the low price and high speed of implementation

Important points of using double spacer:

- Use quality double spacers. Quality double spacers are made of materials that are resistant to wear and corrosion.
- Choose the right size of the double spacer. The size of the double spacer should be large enough to hold the rebar firmly.
- Place the double spacer correctly. The double spacer must be placed perpendicular to the surface.
- By using these tips, you can use the double spacer effectively and create stronger building structures.



Iran, Mashhad, Abu Talib
Crossroads, Barjis Bazaar,
Unit 158



betonbs@gmail.com



09152373401
05137288472



<https://betonbs.com/en/beton-bs/>

