



Beton SHimi  
بتن شیمی زرین کوه



Iran, Mashhad, Abu Talib  
Crossroads, Barjis Bazaar,  
Unit 158



betonbs@gmail.com



09152373401  
05137288472



<https://betonbs.com/en/beton-bs/>



## Heplex Fastener(Beton SHimi)

### Heplex L bracket:

Heplex L bracket is a metal fastener that is used to connect Heplex blocks to each other. These fasteners are made of galvanized steel and due to their special design, they have high strength and resistance.

Technical specifications of the Heplex L bracket	
Type:	Heplex Fastener
Width:	3 cm
Thickness:	2 mm
Application :	Replacement of vestibule connection in AAC walls
product type :	Galvanized steel sheet

### The steps of using the L-plex fastener:

.1Choosing the right fastener:

The first step is to choose the right fastener according to the type of Heplex block and the desired application.

.2Preparation of blocks:

Before installing the fasteners, you need to completely align the Heplex blocks and put them in place. You can use a ruler and a level for this.

.3Fastener installation:

You need a suitable drill to install the Heplex L bracket. First, make a hole with a suitable diameter in the Heplex block at the desired location. Then put the fastener in the hole and tighten it using a drill.

.4Connecting blocks:

After installing the fastener in one block, attach the other block to it. To stick the blocks, you can use a special mortar for Heplex. Spread the mortar thoroughly between the blocks and make sure they are smooth and level.

.5Repeat steps:

Repeat steps 3 and 4 for all blocks in the row.

### The application of Heplex L bracket:

Use in Heplex walls

Use in Heplex roofs

Use in Heplex columns