



Beton SHimi
بتن شیمی زرین کوه

Spacer(Beton SHimi)

Round plastic spacer (Wheel-fix):

A round spacer is a plastic or metal piece that is used to separate two surfaces from each other. These pieces usually have a hole in their center that is used to pass the rod or rod. Round spacers are used in various types of construction and industrial projects.

Technical specifications of the round spacer

Name	Size	Bar size	Packing(QTY)
Wheel – fix 25	25	4-12	800
Wheel – fix 30	30	4-12	800
Wheel – fix 30	30	12-24	400
Wheel – fix 40	40	8-20	250
Wheel – fix 50	50	8-20	200
Wheel – fix 75	75	16-32	100

Advantages of using round plastic spacer:

- Prevention of corrosion of rebars
- Create a suitable concrete cover
- Increasing the strength of the structure
- Reducing the weight of the structure
- Reduce construction costs

Important points when using a round spacer:

- The height of the round spacer must be in accordance with the relevant standards.
- The round spacer must be firmly in place to prevent it from shifting.
- Rebars must be secured in place to prevent deformation.



Iran, Mashhad, Abu Talib
Crossroads, Barjis Bazaar,
Unit 158



betonbs@gmail.com



09152373401
05137288472



<https://betonbs.com/en/beton-bs/>

