



Beton SHimi  
بتن شیمی زرین کوه

## powder coating(Beton SHimi)

### stringing powder 20kg :

Bandage powder is classified into different categories based on the type of compounds used in its construction. Today, due to the importance of plastering powder and its wide application in the interior and exterior of the building, extraordinary features have been added to it and there are various types available in the market. Some powder models have very important efficiency and effectiveness, and their use increases the life of the building.

Technical specifications of 20 kg binding powder	
physical state :	powdery
Color :	Gray
packing :	20 kg
Mixability:	has it
Chlorine ion:	does not have
Maintenance :	away from cold and heat in a closed bucket

### Preparation of binding powder:

Pour about 30% of the weight of the powder into the container with water and add the powder little by little (use a mixer for mixing).

Packing powder: 2, 5, 20 kg

The amount of caulking powder: depending on the size of the tile, thickness and depth of the seam (200 to 500 grams per square meter)

### Uses of binding powder:

- Plumbing of toilets, bathrooms and kitchens
- Strapping of all types of ceramics
- Bricklaying and...
- Stone strapping
- Strapping the interior and exterior of the building and creating more beauty and attractiveness of the work facade
- Tiling of ceramic tiles for the sauna, jacuzzi pool
- To fill all seams up to a depth of 15 ml. Suitable for use in places exposed to high humidity.

Iran, Mashhad, Abu Talib  
Crossroads, Barjis Bazaar,  
Unit 158



betonbs@gmail.com



09152373401  
05137288472



<https://betonbs.com/en/beton-bs/>

